



Safety Requirements

Index

Uniforms	2
Gloves	2
Socks	2
Shoes	2
Arm Restraints	2
Helmets	2
Head and Neck Restraints	2
Headrests	2
Seats	2
Seat Belts	2
Roll Cage Padding	3
Steering Wheel Padding	3
RACEceiver Radios are mandatory	3
Fire Equipment	3
Ending Statement	3

1. Uniforms

- a. All Drivers must wear an approved one-piece racing uniform; complete with fire retardant head sock and/or skirt, socks, gloves, underwear, and shoes.
- b. A driver suit certified to SFI Spec 3.2A/5 is required to be always worn during competition or on the racing surface.

2. Gloves

- a. Gloves certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

3. Socks

- a. Socks certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

4. Shoes

- a. Shoes certified to SFI Spec 3.3 are required to be always worn during competition or on the racing surface.

5. Arm Restraints

- a. Arm restraints are mandatory and must be worn at all times during competition.

6. Helmets

- a. All drivers must wear a full-face helmet.
- b. A helmet certified to Snell SA2015/FIA-8859-2015, Snell SA2020/FIA-8860-2018, SFI 31.1/2015 or SFI 31.1/2020 is required to be always worn during competition or on the racing surface.

7. Head and Neck Restraints

- a. At all times during an event, drivers must connect their helmet to a head and neck restraint device system certified to SFI Spec 38.1.
- b. The head and neck restraint system, when connected, must conform to the manufacturer's mounting instructions, and must be configured, maintained, and used in accordance with the manufacturer's instructions.

8. Headrests

- a. It is mandatory that all cars have a headrest of high impact, shock-absorbing material meeting SFI Specification 45.2 behind the driver's head with a minimum thickness of one (1) inch.

9. Seats

- a. Approved full containment seats are required.
- b. Approved aluminum and composite seats may be used, no fiberglass.
- c. Seats must be mounted with minimum of four (4) bolts 5/16 diameter.
- d. Seats must be installed in accordance with manufacturer's instructions.

10. Seat Belts

- a. Seat belts must be five points and properly attached and/or supported.
- b. Seat belts must meet SFI 16.5 or SFI 16.1, be within manufacturer's expiration label (must have label). Seat belts must be installed and used in accordance with manufacturer's instructions.
 - i. No Y seatbelt mounts will be allowed.
 - ii. No low back seats allowed.
 - iii. No more than two (2) years old.

11. Roll Cage Padding

- a. All chassis protrusions, roll cage tubes and roll bars near the driver's helmet is highly recommended to be padded with a securely attached high impact material conforming to SFI Specification 45.1. This includes any vertical anti-intrusion supports alongside the driver.

12. Steering Wheel Padding

- a. The steering wheel hubs are highly recommended to be padded with resilient material of not less than $\frac{3}{4}$ " thickness.
- b. Right side driver head net is mandatory. Left side is optional. Exception: Full containment seats.

13. RACEceiver Radios are mandatory.

- a. A POWRi Official/Race Director/Division Official reserves the right to penalize and fine drivers that do not run a RACEceiver.
- b. No radio communication to driver except from club or track officials. No rear-view mirrors.

14. Fire Equipment

- a. The Entrant or Crew Chief of each car should have in his pit a fully charged five-pound powder fire extinguisher, or its equivalent. A gauge or current inspection should be attached to each fire extinguisher.
- b. Fire Suppression system is **HIGHLY** recommended and **WILL** be mandated in the future.

15. All race cars and driver's equipment are subject to safety inspections. Tech director reserves the right to refuse a car or driver from competition, if deemed unsafe.